



surrounddecor

4700 lakeside avenue tel 216 | 432 | 1400
third floor free 800 | 496 | 4444
cleveland, ohio 44114 fax 216 | 432 | 1500

inspiring commercial interiors

substrate specifications

commercial grade paper page 2

type II vinyl page 3

premium residential paper page 4

prepasted border paper page 4

canvas page 5

other available substrates page 5

commercial grade paper

Total Weight	6.4 oz/square yard
Roll Width	60 inch
Breaking Strength (Force Newtons Min.) ASTM D-751	
Machine Direction	80
Cross Machine Direction	75
Tearing Strength, Scale ASTM D-751 Pendulum impulse	
Reading Min.	
Machine Direction	36
Cross Machine Direction	30
Colorfastness to Light	200
Blocking, Scale Rating Max.	3
Cold Crack Resistance -20 degree F CCC-W 408D Sec. 4.4.2	No Change
Shrinkage, Percent Max. CCC-W 408D Sec 4.4.1	
Machine Direction	2
Cross Machine Direction	1
Stain Resistance	12
Washability (Double Rubs/Min) ASTM 793-93	100
Scrubbability (Double Rubs/Min) ASTM 793-93	300
Flame/Smoke Testing Certifications	ASTM E-84-98
ASTM E-84-98 Rating*	Class A
Flame Spread Index	25
Smoke Developed Value	50

*(Tested with 1/2" Gypsum Wall Board with Golden Havest #14 Clear Strippable Adhesive)

type II vinyl

Total Weight	20 oz/square yard
Roll Width	54 or 60 inch
Breaking Strength (Force Newtons Min.)	
Machine Direction	50 (222)
Cross Machine Direction	55 (245)
Tearing Strength, Scale	
Reading Min.	
Machine Direction	25
Cross Machine Direction	25
Coating Adhesion, lbs. Force for 1 width, (Newtons for 2.5 cm width)	3 (13.35)
Abrasion Resistance (Double Rubs/Min)	300
Colorfastness to Light	200
Blocking, Scale Rating Max.	2
Crocking, Scale Rating Min	Good
Cold Crack Resistance -20 degree F	No Change
Shrinkage, Percent Max.	
Machine Direction	2
Cross Machine Direction	1
Stain Resistance	1-12
Washability (Double Rubs/Min)	100
Scrubbability (Double Rubs/Min)	300
Flame/Smoke Testing Certifications	NFPA 265, CCCW 408A, CCW408D, MEA No. 404-00-M, ASTM E-84-98
ASTM E-84-98 Rating	Class A
Flame Spread Index	25
Smoke Developed Value	45

premium residential paper

Total Weight	3.96 oz/sq.yard
Roll Width	60 inch
Thickness	6.5 mil
Opacity	96%
Flame/Smoke Testing Certifications	ASTM E-84-98
ASTM E-84-98 Rating	Class A
Flame Spread Index	5
Smoke Developed Value	10

prepasted border paper

Total Weight	4.1 oz/square yard
Maximum Print Width	18.6 inch
Breaking Strength (Force Newtons Min.) ASTM D-751	
Machine Direction	100
Cross Machine Direction	100
Tearing Strength, Scale ASTM D-751 Pendulum impulse	
Reading Min.	
Machine Direction	35
Cross Machine Direction	25
Flame/Smoke Testing Certifications	ASTM E-84-98
ASTM E-84-98 Rating*	Class A
Flame Spread Index	5
Smoke Developed Value	10

*(Tested with 1/2" Gypsum Wall Board with Golden Havest #14 Clear Strippable Adhesive)

canvas

Total Weight	13 oz/square yard
Caliper	15.5-17.0 Mil
Roll Width	63 inch
Coating	Acrylic Coating
Composition	100% Polyester
Whiteness	80 min.
Brightness	84 min.
Color (L*A*B*)	95/0/1.5
Application	Indoors
Coated/Uncoated	Coated for lightfastness

other available substrates

Window Perforated Film/Clear Static Cling

Self Adhesive

Magnetic

Ceiling Tile

Florescent Light Diffusers

Fabric

Backlit

Blinds/Window Shades

Floor Graphics